



LUXOR WHITE

Upright refrigerated display units



Commercial Code	KD8QV
Temperature range	-22/ +5°C
Technical features	<ul style="list-style-type: none"> • Display compartment in tempered glass throughout, with white screen-silk printed glass. • Lower structure in extra clear white tempered glass • A single compartment temperature to positive / negative • Cooling unit at evaporation temperature -23.3°C and condensation temperature 53,5°C rated at 1140 W • Climate Class 4, room +30°C and 55% R.H. • Ventilated refrigeration obtained through evaporator fixed in the ceiling of the display compartment by means of an AISI 304 stainless steel structure • Relative humidity: 65/40% • Automatic defrosting by hot gas • Anti-condense heating elements • Ventilated system on the back with the air circulation not directed straight at food • Refrigerant fluid: R404A • Electronic panel control board with touch keys and HACCP alarms
Functional features	<ul style="list-style-type: none"> • Display shelves in tempered glass. possibility of loading up to 12 kg per shelf. On request available the accessoire KSR25KG: front bearing kit for shelves, to load up to 25 kg • Easily removable magnetic gasket • Glass door with “invisible” full-height handle • Gross internal volume: 490 litri • High brightness LED bar lighting, front panel on the back of the door and on internal ceiling element in the display compartment • Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company • Standard accessories: nr 5 display shelves in tempered glass with the back upright on AISI 304 stainless steel rack • Integrated wheels, hidden by the structure. (nr 4)
External size	80.5x64.5x184cm
Gross/Net weight	243/267 kg
Electrical power	2 kW Standard connection: V-Hz 230V 1N-/50Hz